Silent Camp Hybrid System and Load Profile Sensitivity

Franklin H. Holcomb
Project Leader, Fuel Cell Team
Ph. 217-373-5864

f-holcomb@cecer.army.mil www.dodfuelcell.com

Fuel Cells Science & Technology 2006, Scientific Advances in Fuel Cell Systems Turin, Italy



13 SEP 06

Presentation Outline

- Intro to ERDC
- Problem Statement
- Silent Camp Concept
- Analysis
- Results
- Future Research
- Acknowledgements

Soldiers, Families, and Civilians

Home to the **Force**



Power Projection Training




Work &





... are our Customers!




90 Fuel Cells56 Sites5 Manufacturers



FY01-FY04 Residential Proton Exchange Membrane Fuel Cell (PEMFC) Project Sites


FY93-FY94 Phosphoric Acid Fuel Cell (PAFC) Project Sites



Problem Statement Forward Deployments

- Base Camps and Other Forward Deployments Rely on Diesel (JP8) Fueled Generator Sets (GenSets) which are Inefficient, Noisy, Emit Pollutants, and are High Maintenance
- GenSet Sizes not Optimized for Loads Results in Partial Loading of GenSets → Decreased Efficiency and Increased Maintenance (Wetstacking)
- GenSets Run Continuously 24 Hours / Day, 7 Days / Week
- Cost of Delivered Fuel to Forward Operating Positions Varies from ~ \$40 per Gallon to \$400 per Gallon
- Fuel Supply Lines Difficult to Defend Against Improvised Explosive Devices (IEDs) and Other Attacks → Bigger Issue than Fuel Cost

Forward Deployments



- Base Camps
- Life Support Areas
- Advanced Operations Base
- Forward Operations Base
- Tactical Operations Center
- Etc.








Military GenSets & Efficiency

Current DoD GenSet (2 kW – 60 kW) Inventory

Unit Rating (kW)	No. of Individual Units	Total Capacity (kW)
2	10,979	21,958
3	39,789	119,367
5	17,603	88,015
10	13,745	137,450
15	5,411	81,165
30	6,669	200,070
60	6,495	389,700
Total	100,691	1,037,725



Partial Loading = Very Low Efficiency



3 kW System




30 kW System



60 kW System

Silent Camp Concept

- **Increase GenSet Output to Electrolyze Water**
- **Store H2 Produced from Electrolyzer**
- **Use Stored H2 and Fuel Cell to Power Loads at Night**
- **Shut GenSet Off During Fuel Cell Operation**
- Can Maximize Silent Camp Operation or Fuel Savings




FC Charging ■ Generator Initial Profile \$20 419 813 810 VO VO VO VO PO 813 813 810 Time (24 hr)


24 Hour Load Profile

MATLAB Model Parameters

- Fuel Cell Size (kW)
- GenSet Size (kW)
- Electrolyzer Size (kW)
- Efficiency Curves for Fuel Cell, GenSet and Electrolyzer
- Constant Efficiencies For Storage And Inverter
- Load Profile Input (Demand by Interval-Assumed to Repeat)

Actual Tactical Operations Center (TOC) Load Profile





TOC Profile Results

- Profile Covers 9 Days (216 Hours)
- No Load For 15 Hours → 201 Total Hours Of Load

GenSet Cap. (kW)	Electrolyzer Cap. (kW)	Maximize Fuel Savings		Non Negative Fuel Savings	
		Fuel Savings (Gallons)	Fuel Cell Hours	Fuel Savings (Gallons)	Fuel Cell Hours
30	10	1.98	35	0.14	45
30	30	2.01	62	0.07	76
60	10	23.37	68	21.71	72
60	60	52.06	144	50.97	145

Future Research

- Maximize Overall Fuel Savings (Regardless of Number of Hours of Silent Camp Operation)
- Real-Time Control Strategy With Load Forecasting
- Active Wetstacking Protection (Force GenSet Loads ≥ 50%)
- Quantify Water Requirements
- Quantify Maintenance Savings
- Find Optimum GenSet Electrolyzer Fuel Cell Combinations
- Allow System to Produce Additional H2 for Other Uses

Acknowledgements

 Mr. Joe Bush, ERDC-CERL for the Silent Camp Algorithm Development & MATLAB Programming



Dr. Jack Brouwer and Mr. Tim Brown (Ph.D. Student) at the University of CA – Irvine, National Fuel Cell Research Center (NFCRC) for Consultation and Review





The 249th Engineer Battalion for their Proponency of the Silent Camp Concept



www.dodfuelcell.com

